

# Accesorii hidraulice

Folosind un motor hidraulic, zgomotul produs este minim  
 Maxima eficienta  
 Mentenanta usoara cu o eficienta maxima  
 Mobilitate marita datorita dimensiunilor reduse, se poate lucra si in spatii inguste

<b>Fierastrau circular</b>	<b>CH 130</b>
Debit	20 l/min.
Rotatii	3200 rpm
Diametru disc	Ø 300 mm
Diametru gaura prindere	Ø 20 mm
Greutate	12.4 kg
Dimensiuni L/l/h (mm)	430x275x190



<b>Pompa submersibila</b>	<b>PH 301</b>
Diametru refulare	Ø 75 mm
Debit	780 l/min.
Presiune max.	1.5 bar
Inaltime refulare	20 m
Granulometrie	9.5 mm
Rotatii	3200 rpm
Debit ulei	20 - 25 l/min.
Greutate	12.4 kg
Dimensiuni L/l/h (mm)	430x275x190



Inaltime de pompare 20 m  
 Ideala pentru lucrari civile,  
 avand o greutate redusa



Echiptat cu un acumulator ce confera o putere de demolare excelenta  
 Zgomot redus cu mai putine vibratii  
 Nu are restrictii de functionare in anotimpul rece  
 Picon lubrefiat, nu necesita lucrari de mentenanta  
 Dimensiuni compacte, picoane usoare si eficiente

<b>Picon hidraulic</b>	<b>BH 112V</b>	<b>BH 161V</b>	<b>BH 201V</b>
Debit ulei	15 - 20 l/min.	18 - 22 l/min.	15 - 20 l/min.
Frecventa batai	1450 /min.	1650 /min.	1050 /min.
Dimensiune spit	7/8" x 83mm	7/8" x 108 mm	1 x 154 mm
Greutate	13 kg	16.5 kg	26 kg



Nacele

**SOLICITA ACUM  
 OFERTA  
 PERSONALIZATA!**

Italia Star Com Due S.R.L.  
 Autostrada Bucuresti - Pitesti km. 13.2  
 Loc. Chiajna - Ilfov  
 Tel: 021.433.03.27  
 Fax: 021.433.03.26  
 info@italiastar.ro www.italiastar.ro