

Generator de curent stationar cu automatizare la pornire



| Generator | SKD34S |
|------------------------------|-----------------------|
| Putere max. generator | 34 kVA / 27 kW |
| Putere generator continua | 31,3 kVA / 25 kW |
| Voltaj | 400 / 230 V |
| Frecventa | 50 Hz |
| Factor de putere | 0,8 |
| Amperaj | 47,5 A |
| Panou ATS | Inclus in standard |
| Motor | YS4100D |
| Putere motor | 33 cp |
| Turatie motor | 1.500 rpm |
| Nr. cilindri motor | 4 vertical in linie |
| Aspirare aer | Normala |
| Preincalzire motor | Inclus in standard |
| Racire motor | Lichid racire |
| Capacitate lichid racire | 10 l |
| Carburant | Motorina |
| Consum la 25% din putere | ≤ 235 g / kW / h |
| Autonomie la 70% putere | 25 ore |
| Capacitate rezervor | 100 l |
| Tip ulei | 15W40 |
| Capacitate rezervor ulei | 8 l |
| Consum maxim de ulei | 0,25 % |
| Numar poli | 4 |
| Regulator de tensiune | AVR |
| Regulator turatie motor | Mecanic |
| Precizia tensiunii de iesire | ± 1% |
| Nivel zgomot la 7 metri | 80 dB |
| Greutate | 971 kg |
| Dimensiuni LxIxh (mm) | 2.250 x 1.000 x 1.250 |

Model: SKD34S



Controller DC5x-4G Ver1.0

Dotare standard panou pentru automatizare la pornire tip ATS-M

Optional prize pe panoul de comanda:

1 x 400V 63A

1 x 400V 32A

1 x 230V 16A

Protectie generator IP32

Temperatura de lucru -15° + 70°C

Temperatura depozitare -30°C +80°C



www.italiastar.ro



Italia Star Com Due S.R.L.
Autostrada București - Pitești km. 13.2
Loc. Chiajna - Ilfov
Tel: 021.433.03.27
Fax: 021.433.03.26
info@italiastar.ro www.italiastar.ro

