

Generator de curent stationar cu automatizare la pornire



| Generator | BIFA88 |
|------------------------------|---------------------------|
| Putere max. generator | 88 kVA / 70 kW |
| Putere generator continua | 80 kVA / 64 kW |
| Voltaj | 400 / 230 V |
| Frecventa | 50 Hz |
| Factor de putere | 0,8 |
| Panou ATS | Inclus in standard |
| Regulator de tensiune | AVR |
| Motor | IVECO / N45SM3 |
| Demaraj | Electric |
| Turatie motor | 1.500 rpm |
| Nr. cilindri motor | 4 vertical in linie |
| Aspirare aer | Turbocharger |
| Preincalzire motor | Inclus in standard |
| Racire motor | Apa |
| Capacitate lichid racire | 18,5 l |
| Carburant | Motorina |
| Consum sub 50% sarcina | 12,8 l/h |
| Capacitate rezervor | 140 l |
| Capacitate rezervor ulei | 12,8 l |
| Numar poli | 4 |
| Tip alternator | Autoexcitatie, fara perii |
| Regulator turatie motor | Electronic |
| Precizia tensiunii de iesire | ± 1% |
| Clasa izolare | H |
| Clasa protectie | IP23 |
| Greutate | 1.310 kg |
| Dimensiuni Lxlxh (mm) | 2.350 x 1.100 x 1.730 |

Model: BIFA88



Controller ALM 929

Distribuitor local