

APD11000Q



Panou ATS inclus
in echiparea standard

Generator	APD11000-Q
Plaja tensiune	230 / 400v
Putere Max.	8 kW / 8 kW
Putere nominala	7 kW / 7 kW
Plaja frecventa	50 Hz
Model motor	Senci 198
Demaraj	electric
Capacitate cilindrica	633 cc
Combustibil	Diesel
Capacitate rezervor	15 l
Consum combustibil	≤2,3L/h
Capacitate rezervor ulei	1,65 l
Temperatura mediului	≤40°C
Factor de putere	COSφ=1
Nivel de izolare	F
Nivel zgomot @7m (dB)	78-81
Greutate	195 kg
Dimensiuni LxIxh (mm)	1110x630x850

Echipare standard:

- Contor 5 in 1: ore, voltmetru, frecventa, amperaj si kW
- Alternator Senci de calitate superioara cu dubla infasurare mono si trifazic
- Alerta nivel ulei scazut cu oprire automata a motorului
- Senzor de suprasarcina cu auto-oprire
- Silentios si prietenos cu mediul
- Compact, cadru rezistent
- Interior captusit cu burete fonoabsorbant din spuma poliuretana flexibila pentru o izolare fonica sporita
- Pentru uz casnic dar si comercial
- Panou de control rezistent la ploaie si praf
- Intrerupator circuit ce opreste alimentarea atunci cand sistemul este suprasolicitat
- Echipat cu roti pentru o mai buna deplasare



Distribuitor local

Generator de curent

APD11000Q



Contor 5 in 1: ore, voltmetru, frecventa, amperaj, kW

Siguranta suprasarcina

Incalzire aer

Senzor lipsa ulei

Circuit breaker

Buton ON/OFF

Conexiune ATS

Priza monofazica 16 Ah 230V

Priza trifazica 16 Ah 400V

Protectie termica

Comutator 230V-400V



Distribuitor local