

Generator de curent stationar cu automatizare la pornire



Generator	SKD25S
Putere max. generator	25.0 kVA / 19.8 kW
Putere generator continua	22.5 kVA / 18.0 kW
Voltaj	400 / 230 V
Frecventa	50 Hz
Factor de putere	0,8
Amperaj	32,4 A
Panou ATS	Inclus in standard
Motor	YS490D
Putere motor	21 cp
Turatie motor	1.500 rpm
Nr. cilindri motor	4 vertical in linie
Aspirare aer	Normala
Preincalzire motor	Inclus in standard
Racire motor	Lichid racire
Capacitate lichid racire	9 l
Carburant	Motorina
Consum combustibil	≤ 235 g / kW / h
Autonomie la 70% putere	30 ore
Capacitate rezervor	86 l
Tip ulei	15W40
Capacitate rezervor ulei	4 l
Consum maxim de ulei	0,25 %
Numar poli	4
Regulator de tensiune	AVR
Regulator turatie motor	Mecanic
Precizia tensiunii de ieșire	± 1%
Nivel zgomot la 7 metri	80 dB
Greutate	669 kg
Dimensiuni LxIxh (mm)	1.950 x 900 x 1.050

Model: SKD25S



Controller DC5x-4G Ver1.0

Dotare standard panou pentru automatizare la pornire tip ATS-M

Optional prize pe panoul de comanda:

1 x 400V 63A

1 x 400V 32A

1 x 230V 16A

Protectie generator IP32

Temperatura de lucru -15° + 70°C

Temperatura depozitare -30°C +80°C



www.italiastar.ro



Italia Star Com Due S.R.L.
Autostrada București - Pitești km. 13.2
Loc. Chiajna - Ilfov
Tel: 021.433.03.27
Fax: 021.433.03.26
info@italiastar.ro www.italiastar.ro

