

Placa compactoare unidirectionala



Echipament
ansamblat
in Romania

PC70

Utilizare:

Compactare balastru, pavele de beton, asfalt, pamant, agregate etc.



Powered by

HONDA
POWER EQUIPMENT

LONCIN

Motorizare, consumabile si
piese de schimb originale



Motorizare in 4 timpi, racire cu aer, alimentare cu benzina
Maneta de acceleratie si shock heavy-duty
Maner pliabil cu manson de protectie la vibratie
Talpa turnata din fonta
Colturi rotunjite ale talpii
Datorita manerelor pliabile si rotilor din dotare, se poate
transporta usor si ocupa un spatiu redus

Dotare de serie:

Covor cauciuc pentru pavele
Kit roti pentru transport
Rezervor de apa

Placa compactoare	PC70-H	PC70-L
Tip motor	Honda GX160	Loncin G200F
Combustibil	Benzina	Benzina
Putere motor	5.5 cp	6.5 cp
Capacitate rezervor	3.1 l	3.6 l
Frecventa vibratii	5600 vpm	5600 vpm
Dimensiune talpa (mm)	500 x 360	500 x 360
Forta de compactare	11.5 kN	11.5 kN
Adancime max. de compactare	250 mm	250 mm
Eficienta compactare	450 m ² /h	450 m ² /h
Viteza de inaintare	40 cm/s	40 cm/s
Nivel de zgomot	99 dB	99 dB
Greutate utilaj	65 kg	65 kg
Dimensiuni LxIxh (mm)	1060x360x970	1060x360x970

Distribuitor local